

L4100

触变树脂

特性

- 1、铝粉定向排列
- 2、防沉降性能

用途

可以用于大、中巴车、摩托车、汽车修补漆以及运输工具用金属底漆，塑胶、家具等铜、铝、珍珠漆。

性质

特性	数值	单位
组份	乙烯醋酸乙烯共聚溶液	
外观	乳白色液体	
固体份	6.5±0.5	%
溶剂	BAC/XYL/异丁醇	

储存说明

- 远离热及火源，置于阴凉通风处，容器保持紧密。
- 本产品自生产日起，保质期限为 12 个月。

包装规格

50Kg/桶或 180Kg/桶

安全

本产品含溶剂，必须做好防护措施，小心操作，避免接触皮肤与眼睛，其它详细资料请参考物质安全说明书。

以上资料系经试验所得，仅供参考，不作任何保证之用。鉴于树脂功能的局限性及用户要求的多样性，若使用本公司产品，使用前请按自身的要求严格试验树脂的适应性及最终产品的稳定性。

版本：2024-8-26

L4100

Thixotropic resin

Characteristics

- 1、Aluminum directional configuration
- 2、The function of preventing sedimentation

Application

Used for large and middle-sized buses,motorcycle,automotive refinish and transport tools with metal primer. Plastic, furniture and other items use copper, aluminum, pearl paint.

Property

Characteristics	Numeric value	Unit
Component	EVA resin solution	
Appearance	Milky white liquid	
Solid Content	6.5±0.5	%
Solvent	BAC/XYL/IBA	

Storage instructions

- Keep away from fire and heat, placed in a cool and ventilated place, Keep the container tightly sealed
- Shelf time:12 months.

Packing

50Kg/Bucket and 180Kg/Bucket

Safety

This product contains solvent, you must take protective measures , avoid contacting with skin and eyes, other information please refer to the material safety instruction.

The above information is obtained through experiments. It is provided for reference only. Given the limitations of resin functionality and the diversity of user requirements.If you use our products, please strictly verify according to your own requirements .Please strictly test the adaptability of the resin and the stability of the final product according to your own requirements.

Version: 2024-8-26

Jiafu Industrial Zone Yinshan Industrial Park high-tech zone Qingyuan City Guangdong Province China

Tel: 0763-3607328 E-mail: liushul@yakoo.com.cn [Http://www.yakoo.com.cn](http://www.yakoo.com.cn)